



County of Spotsylvania
Procurement Division

8800 Courthouse Road (P.O. Box 215)
Spotsylvania, VA 22553
Ph. 540/507-7586 Fax 540/582-6304

PURCHASE ORDER

PURSUANT TO
VIRGINIA CODE §2.2-4343.1,
SPOTSYLVANIA COUNTY DOES NOT
DISCRIMINATE AGAINST FAITH-
BASED ORGANIZATIONS

P.O. NUMBER 17077

P.O. number must appear on all related correspondence, shipping papers, and invoices:

To: Laake Enterprises, dba Fesco Emergency Sales **Ship To: Spotsylvania County Fire, Rescue & Emergency Management**
7010 Troy Hill Drive **9119 Dean Ridings Lane**
Elkridge, MD 21075 **Spotsylvania, VA 22553**

Attn: Michael Seabright

Attn: Jay Cullinan

		SHIP VIA	F.O.B. POINT	TERMS	
April 11, 2017			Destination	Net 30 Days	
QTY	UNIT	DESCRIPTION		UNIT PRICE	TOTAL
3	EA	2017 Model Year Horton #603F Type I Ambulances mounted on 2017 Ford F550, 4x4 cab and chassis. Contract documents consist of and are incorporated herein: 1. County of Spotsylvania Purchase Order #17007 dated April 11, 2017 and Spotsylvania County Purchase Order General Terms & Conditions dated August 9, 2016; 2. Fesco Emergency Sales Selected Feature List #15147 dated January 19, 2017; 3. Fesco Emergency Sales Schedule "A" Contract number FES-00-14JH with the County of Orange, VA dated April 30, 2014; Orange County, Virginia Contract Lease Agreement Modification Form Number 1 Dated March 10, 2015; Orange County, Virginia Contract Lease Agreement Modification Form Number 2 dated February 24, 2016. 4. Fesco Emergency Sales RFP #2014-06 Type I & Type III, Ambulance Design & Purchase submitted by Fesco Emergency Sales signed and dated on January 14, 2014; 5. County of Orange, Virginia, RFP #2014-06 Ambulance Design & Purchase Fire Department dated December 17, 2013.		\$250,857.00	\$752,571.00
TOTAL					\$752,571.00

If there are any questions concerning this purchase order, please contact Ms. Donna Beasley – Spotsylvania County Procurement Division. Ph. 540/507-7586; Fax: 540/582-6304

1. Please send one copy of your invoice.
2. In accordance with the prices, terms, delivery method, and specifications, including warranties, pursuant to any IFB and bid documents, or referenced Terms & Conditions delineated above.
3. Delivery constitutes acceptance of all terms and conditions.
4. Please notify us immediately if you are unable to ship as specified.
5. Send all invoices to:
Spotsylvania County FREM
P O Box 818
Spotsylvania, VA 22553
6. Pursuant to Virginia Code §2.2-4311.1, seller warrants that during the performance of this contract, it will not employ unauthorized alien workers, as defined by the Immigration Reform and Control Act of 1986.

FOR OFFICIAL USE ONLY

Requisitioning Department: FREM
Requisitioner: Jay Cullinan

Mark B. Taylor
County Administrator

Approved as to form 
County Attorney

This standard Purchase Order form has been previously APPROVED AS TO FORM by the Office of the Spotsylvania County Attorney for small purchases. Any deviations from the County's customary form must be reviewed and approved by the County Attorney



SPOTSYLVANIA COUNTY PURCHASE ORDER GENERAL TERMS AND CONDITIONS

1. All prices unless otherwise specified are F.O.B. Destination with transportation charges prepaid.
2. If shipment is made by freight or express and charges added to invoice, the original bill of lading properly receipted shall accompany invoice. All charges must be prepaid.
3. Deliveries against this order must be free of excise, transportation, or state sales taxes. State sales and use tax certificate of exemption form will be issued upon request.
4. Purchase Order number shall be shown by Contractor on all related invoices, delivery memoranda, bills of lading, packages and/or correspondence.
5. Invoice terms are Net 30 days.
6. The CONTRACTOR providing services to the County under this Purchase Order Agreement represents and warrants to the County that it is:
 - A. Conforming to the provisions of the Civil Rights Act of 1964, as amended, as well as the Virginians With Disabilities Act, the Americans With Disabilities Act and Section 2.2-4311 of the Virginia Public Procurement Act, and where applicable, to the Virginia Fair Employment Contracting Act of 1975, as amended, and the Virginia Human Rights Act, as amended.
 - B. Not employing illegal alien workers or otherwise violating the provisions of the Immigration Reform and Control Act of 1986 and Virginia Code § 2.2-4311.1;
 - C. Complying with federal, state and local laws and regulations applicable to the performance of the goods and services procured, the work performed pursuant to the Agreement shall conform to all professional principles generally accepted as standards of the industry in the Commonwealth, the CONTRACTOR'S work performed shall be free of defects, and any new materials and equipment furnished under this Agreement shall be of good quality and in working condition; and
 - D. In full compliance with the Virginia Conflict of Interest Act.
7. CONTRACTOR'S performing work for the County shall maintain at a minimum, the following insurance coverage, if the work is performed by any type of corporation, partnership, or licensed business. An Automobile liability policy may be under a personal policy for a sole proprietor.
MINIMUM INSURANCE COVERAGES AND LIMITS REQUIRED:
 - A. Worker's Compensation – Statutory requirements and benefits
 - B. Employers Liability - \$100,000
 - C. Commercial General Liability - \$1,000,000 Combined Single Limit Bodily Injury and Property Damage Each Occurrence. These coverages are to include Products/Completed Operations, Personal & Advertising Injury, and Independent Contractor's Liability
 - D. Automobile Liability \$500,000.
 - E. Professional Liability, if required, under Professional Services.The County, Board of Supervisors and employees, shall be named as additional insured on Auto and General liability Policies. The County reserves the right to require the Contractor to provide evidence of required insurance coverage.
8. During the performance of this Agreement, CONTRACTOR agrees that:
 - A. It will not discriminate against any employee or applicant for employment because of race, religion, color, sex, national origin, age, disability, or any other basis prohibited by state law relating to discrimination in employment, except where there is a bona fide occupational qualification reasonably necessary to the normal operation of the Contractor; that it will post in conspicuous places, available to employees and applicants for employment, notices setting forth the provisions of this nondiscrimination clause; and that it will state, in all solicitations or advertisements for employees placed by or on behalf of the Contractor that such Contractor is an equal opportunity employer. Notices, advertisements and solicitations placed in accordance with federal law, rule or regulation shall be deemed sufficient to meet this requirement; and
 - B. It will include the provisions of the foregoing paragraph in every subcontract or purchase order of over \$10,000.00, so that the provisions will be binding upon each sub-CONTRACTOR or CONTRACTOR.

8. During the performance of this Agreement, the CONTRACTOR agrees to:
- A. Provide a drug-free workplace for the CONTRACTOR'S employees; and comply with the Federal Drug Free Workplace Act.
 - B. Post in conspicuous places, available to employees and applicants for employment, a statement notifying employees that the unlawful manufacture, sale, distribution, dispensation, possession, or use of a controlled substance or marijuana is prohibited in the CONTRACTOR'S workplace and specifying the actions that will be taken against employees for violations of such prohibition;
 - C. State in all solicitations or advertisements for employees placed by or on behalf of the CONTRACTOR that the CONTRACTOR maintains a drug-free workplace; and
 - D. Include the provisions of the foregoing clauses in every subcontract or purchase order of over \$10,000, so that the provisions will be binding upon each SUBCONTRACTOR or CONTRACTOR.
 - E. For the purposes of this section, "drug-free workplace" means any site at which the performance of work is done in connection with this contract awarded to the CONTRACTOR, the employees of whom are prohibited from engaging in the unlawful manufacture, sale, distribution, dispensation, possession or use of any controlled substance or marijuana during the performance of the contract.
10. The parties agree that this Agreement is governed by and shall be interpreted in accordance with the laws of the Commonwealth of Virginia, and that proper venue, in the event of litigation concerning this matter, shall be in the Circuit Court of Spotsylvania County, Virginia. The parties agree that any litigation involving this Agreement shall be brought only in such court. In the event of any action brought by either party against the other to enforce any of the obligations hereunder or arising out of any dispute concerning the terms and conditions hereby created, each party shall pay their own attorney's fees, costs and expenses.
11. Pursuant to Section 2.2-4354 of the Code of Virginia, (1950, as amended), the CONTRACTOR covenants and agrees to:
- A. Within seven (7) days after receipt of any amounts paid to the CONTRACTOR under the Agreement, (i) pay any subcontractor for its proportionate share of the total payment received from the COUNTY attributable to the work under the Contract performed by such subcontractor, or (ii) notify the COUNTY and the subcontractor, in writing, of its intention to withhold all or part of the subcontractor's payment and the reason therefore;
 - B. Provide its federal employer identification number or social security number, as applicable, before any payment is made to the CONTRACTOR under the Agreement;
 - C. Pay interest at the legal rate or such other rate as may be agreed to in writing by the subcontractor and the CONTRACTOR on all amounts owed by the CONTRACTOR that remain unpaid after seven (7) days following receipt by the CONTRACTOR of payment from the COUNTY for work performed by the subcontractor under the Agreement; and
 - D. Include in its contracts with any and all subcontractors the requirements of 1, 2, and 3 above.
12. CONTRACTOR shall indemnify, defend and hold harmless the COUNTY and its representatives from any and all claims, suits and actions for injury or damage sustained by any person or property from any act or omission by CONTRACTOR and/or its CONTRACTORS or employees, or anyone else for whom CONTRACTOR is or may be responsible. This section shall survive the termination of this Agreement.
13. Spotsylvania County reserves its rights of ownership to all material given to the Contractor by Spotsylvania County and to all background information, documents, and computer software and documentation developed by the Contractor in performing any Contract resulting from this procurement.
14. Spotsylvania County shall have the right to terminate at Spotsylvania County's convenience, with or without cause, any contract resulting from this Purchase Order by specifying the date of termination in a written notice. In this event, the Contractor shall be entitled to just and equitable compensation for any authorized satisfactory work done or any items/materials accepted by Spotsylvania County.
15. CONTRACTOR acknowledges that the Spotsylvania County Procurement Policy is applicable to this Agreement. The Spotsylvania County Procurement Policy governing this Agreement may be accessed at:
<http://www.spotsylvania.va.us/content/20925/20963/21966/20995/23291/default.aspx>



FESCO Emergency Sales--6401 Macaw Court--Elkridge, Maryland 21075

COUNTY OF SPOTSYLVANIA

PO BOX 215

SPOTSYLVANIA, VIRGINIA 22553

DONNA BEASLEY

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Type: 1
Model: 603F

Rev 3 Print Features

15147

CATEGORIES:

A	Chassis
B	Body Connection Pass Thru Type
BH	Chassis Accessories
BL	Chassis Electrical
C	Conversion Model
CB	Module Body Modifications
D	Module Body Hardware
E	Paint and Striping
F	Cabinet Doors, Handles and Hardware
G	Interior Colors
H	Interior Cabinets, Streetside
I	Interior Cabinets, Curbside
J	Front Wall Cabinets
K	Interior Accessories and Trim
L	Cot Mount, and Patient Handling
M	Warning Systems, Visual
MN	Warning Systems, Audible
O	Lights, Non Emergency
P	Electrical Power Group
Q	Heat, Ventilation, Air conditioning
R	Console, Radio, and communications
T	Oxygen and Suction
U	Lettering and Graphics
Z	Other

Prepared By: Michael Seabright

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

AB			Horton Emergency Vehicles Feature List	
----	--	--	--	--

AC			CHASSIS	
----	--	--	---------	--

AFF 1 1 FORD F-SERIES CHASSIS

AFF64016 0 1 CHASSIS, 2016 FORD 4X4, 189" F-550 CAB/CHASSIS

The chassis required to complete the ambulance conversion shall be supplied by Horton.

1/3/2017 The chassis shall be a 2017 model year.

The chassis shall be supplied with Ford OEM polished aluminum front and outer rear wheels.

AFFSP001 0 1 FORD F-SERIES SPECIAL INSTRUCTION

1/3/2017 !!! FORD FIN CODE #QC691.

AFFSP002 0 1 FORD F-SERIES SPECIAL INSTRUCTION

1/3/2017 The chassis shall be supplied with Ford OEM polished aluminum front and outer rear wheels.

AJNSPIC0 1 1 CHASSIS INTERIOR COLOR SHALL BE GRAY

B			CHASSIS MODIFICATIONS, HARDWARE AND ACCESSORIES	
---	--	--	---	--

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
BH010000	1	1	DIESEL EXHAUST FLUID (DEF) The fill for the DEF tank will be located in the driver's side of the body forward of the rear wheels. A lable stating "DIESEL EXHAUST FLUID (DEF)" will be installed next to the fill neck. (Option is applicable to 2011 and later Ford F-series chassis)	
BH03B000	1	1	MUD FLAPS: rear Install individual rear mud flaps behind each set of rear wheels. 12/30/2013	
BH08H000	0	1	RUNNING BOARDS: STAR PUNCHED Install heavy duty aluminum diamond plate running boards and splash shields. Running boards are to be star punched for enhanced drain and foot grip. 12/23/2013	
BH10B000	0	1	REAR TOW HOOKS Install (2) tow hooks rear of vehicle. Attach to bumper frame. 11/2/2012	
BH110000	1	1	REAR STEP/ BUMPER ASSEMBLY The center section of the rear step bumper shall be constructed of aluminum grip strut and be hinged to assist in patient handling.	
BH16L000	1	1	LIQUID SPRING SUSPENSION WITH DUMP FEATURE A Liquid Spring rear suspension shall be installed. The suspension system shall dump when the left rear entry door is opened. The system shall include a dump override switch. 12/18/2015 LOCATE: INNER PANNEL OF THE RIGHT REAR ENTRY DOOR	
BH32OR00	1	1	SUSPENSION SWITCH: dump override A switch will be installed where specified, to override the automatic dump feature activated by the left rear patient compartment entry door. 12/18/2015 LOCATE: INNER PANNEL OF THE RIGHT REAR ENTRY DOOR NOTE: LEGEND TO READ "DUMP OVER RIDE"	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
BHSPD006	0	1	MIRROR: OEM The mirror set shall be OEM supplied, and installed by the chassis manufacturer. 7/12/2003	
BL073000	1	1	BATTERIES, STANDARD ON F-SERIES FORD CHASSIS (2) OEM batteries shall be installed in the manufacturers under hood battery tray locations.	
BL08A000	1	1	BATTERY HEAT SHIELDS Battery heat shields will be provided for any battery located under the hood which is not protected by the OEM manufacturer.	
BL26B000	1	1	BACKUP ALARM RESET Backup alarm to automatically reset to on if alarm was manually canceled using the control panel alarm cut-off switch (FL25) during previous use.	
BL32A000	1	1	OEM AM/FM/CD PLAYER SHALL BE PROVIDED BY THE OEM MANUFACTURER OEM AM/FM/CD player shall be provided by the OEM manufacturer on all Horton supplied chassis. <i>Note: This option applies only to chassis supplied by Horton. Chassis supplied by either the customer or the dealer must be ordered with this feature from the chassis OEM.</i>	

C CONVERSIONS

CA200000	0	1	PREVIOUS VEHICLE REFERENCE This option is to be used for comparison purposes only. Specifications are specific to each order so use extreme caution when referencing a previous production order. 1/8/2017 PREVIOUS VEHICLE PRODUCTION #17415/18	
----------	---	---	---	--

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

CA594000 0 1 CONVERSION MODEL: 603F FORD F SERIES

MINIMUM BODY DIMENSIONS:

(Exterior)
-Height: 92"
-Width: 96"
-Length: 167"
(Interior)
-Height: 72"
-Aisle 20"
-Width: 20" (from edge of cot in wall position to squad bench riser)
-Length: 163"
OVERALL DIMENSIONS (Including Chassis, Module and Step):
-Height: 117" (to top of vent)
-Width: 100"
-Length: 301"

5/11/2015

CA594001 1 1 F603 STREETSIDE FORWARD:

Clear Door Opening: 18.7" wide x 79.1" high
Actual Compartment 24.2" wide x 82.1" high x 20.3"
This area shall be accessed through a single outside hinged door.
The compartment shall house the vehicle's primary O2 cylinder. The compartment shall be vented to the outside.

2/16/2016 !!! NOTCH FOR COOLTECH III.

0 1 DIVIDER FIXED, VERTICAL COMPARTMENT

dr11a000 Install a 16" deep fixed vertical divider shall be installed in the location listed below. (Divider material is to match the compartment material)

5/21/2014 Locate: 11.5" FROM RIGHT WALL

CA594002 1 1 F603 STREETSIDE INTERMEDIATE:

Clear Door Opening: 51.7" wide x 38.3" high
Actual Dimensions: 55.5" wide x 41.5" high x 20.3"
This area shall be accessed through double, outside hinged doors.
Both doors shall have exterior door handles and latching devices.

2/16/2016 !!! COMPARTMENT TO BE 2" HIGHER PER NEW STANDARD.

!!! INSTALL PD BOX AND ROTATE CLOSEOUT PER HORTON STANDARD.

0 1 SHELF FOR LED LIGHTED DOUBLE DOOR COMPARTMENT

dr09lb00 A diamond plate adjustable shelf shall be installed in the area listed below.

5/21/2014

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
	0	1	EXPANDED METAL CAGE FOR PROTECTION OF EQUIPMENT	
dr11ca00			Install an expanded metal cage around the onboard electrical equipment per location noted below. Include access ports to equipment with grip lock around the edges of the openings.	
			5/21/2014 LOCATE: CEILING	
CA594004	1	1	F603 STREETSIDE REAR:	
			Clear Door Opening: 26.0" wide x 58.3" high	
			Actual Dimensions: 30.6" wide x 61.5" high x 20.3"	
			This area shall be accessed through double, outside hinged doors.	
			Both doors shall have exterior door handles and latching devices:	
			3/9/2016 !!! COMPARTMENT TO BE SINGLE DOOR ILOS.	
	0	1	COMPARTMENT HEIGHT Modify: first, street side	
cb040000			The height of the standard compartment for this model shall be modified. This is the first street side compartment height modification and shall include affected modifications to the interior cabinet.	
			5/21/2014 Height Modification: DECREASE 20"	
	0	1	SHELF FOR LED LIGHTED VERTICAL COMPARTMENT	
dr08l000			A diamond plate adjustable shelf shall be installed in the following location.	
			2/16/2016 !!! DECREASE DEPTH OF SHELF TO CLEAR TOOL BOARD	
	0	1	TOOL MOUNTING PLATE	
dr10d000			A .250" thick aluminum plate with a sanded D/A finish shall be installed in the designated area. The plate will be secured to the compartment wall using existing or additional extruded aluminum "C" channels.	
			2/16/2016 SIZE: AS LARGE AS POSSIBLE	
			LOCATION: BACK WALL	
	0	2	EXTRUDED ALUMINUM "C" CHANNEL, ADDITIONAL	
dr10e000			Additional section of aluminum "C" channel shall be installed on the designated compartment walls. Standard tool boards require two C-channels.	
			5/21/2014 Location: BACK WALL FOR TOOL PLATE	
CA594005	1	1	F603 CURBSIDE REAR:	
			Clear Door Opening: 19.0" wide x 79.1" high	
			Actual Dimensions: 23.7" wide x 82.1" high x 20.3"	
			This area shall be accessed through a single outside hinged door	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
	0	1	DIVIDER FIXED, VERTICAL COMPARTMENT	
dr11a000			Install a 16" deep fixed vertical divider shall be installed in the location listed below. (Divider material is to match the compartment material)	
	6/30/2014		Locate: 12" FROM RIGHT WALL	
CA594006	1	1	F603 CURBSIDE FORWARD:	
			Clear Door Opening: 22.1" wide x 79.1" high	
			Actual Dimensions: 27.2" wide x 82.1" high x 28.5"	
			This area shall be accessed through a single outside hinged door and from an opening located on the curb side forward wall. The area shall be primarily used for storage of customer furnished jump kits.	
	0	1	CLOSEOUT, EXTERIOR COMPARTMENT	
dr11cl00			Install a closeout to block off exterior access to the exterior compartment as noted below. Fabricate closeout to match compartment material.	
	5/21/2014		Locate: SO THERE IS NO OUTSIDE ACCESS TO UPPER PORTION OF FRONT WALL CABINET	

CB BODY MODIFICATIONS/OPTIONS

CB06SX00	0	1	DOUBLE STEP CURBSIDE ENTRY 6" DROP SKIRT	
			The curbside skirt, forward of the rear wheel well shall be dropped 6 inches. Two integral ALD steps within the side patient door step well shall be available upon opening the side door for easier and lower access to the patient compartment.	
	5/11/2015			
CB09SA00	1	1	PATIENT AREA SOUND PROOFING/ACOUSTIC ENHANCEMENT PACKAGE	
			Install standard sound control package.	
	1/10/2014			
CB120000	0	1	POCKET FOR COOL TECH II	
			Modify the body roof structure for installation of a Cool Tech II condenser to be recessed into the forward portion of the roof.	
	2/16/2016		!!! ILOS, COOL TECH III	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

CBSP0001 0 1 SPECIAL INSTRUCTION, BODY MODIFICATIONS

2/16/2016 !!! NOTE GLOVE BOX STORAGE OVER SIDE ENTRY DOOR. MODIFY HEIGHT OF DOOR AS NECESSARY.

CBSP0002 0 1 SPECIAL INSTRUCTION, BODY MODIFICATIONS

6/2/2015 !!! ILOS ALL ICC MARKER LIGHTS TO BE TRUCK-LITE #35375R OR Y AS REQUIRED BY LAW.
!! THE LICENSE PLATE LIGHT TO BE A TECNIQ #L11-WC00-1.

D MODULE BODY HARDWARE

DG05C100 0 1 PRIVACY WINDOWS, REAR MODULE BODY ENTRY DOORS

The rear module entry doors shall have solid windows. The windows shall have dark privacy glass. The windows shall meet FMVSS glazing standards. No films are to be used.

6/2/2015

DG06C200 0 1 PRIVACY WINDOW, SLIDING FOR SIDE ENTRY DOOR

The side entry door shall have a sliding window. The window shall have dark privacy glass. The window shall meet FMVSS glazing standards. No films are to be used.

6/2/2015

DG080000 1 1 EMERGENCY DOOR RELEASE MECHANISM, REAR DOORS

Install standard emergency release knobs on top and bottom of rear module entrance doors.

DG08A000 1 1 DOOR HANDLES

Install Tri-Mark free floating style door handles with pre-stretched stainless steel cables. Include three piece interior door panels on all access doors.

DH000000 1 1 Vi-Tech body mounts

Install standard Vi-Tech body mounts.

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
DH03B000	1	1	MIRROR STAINLESS STEEL SPLASH SHIELDS Install #8 mirror stainless splash shields on the lower front face of the body just behind the cab access doors. These splash shields are to be the same height as the diamond plate front corner guards. 1/5/2007 (NOT AVAILABLE ON FORD "E" SERIES CHASSIS IN CONJUNCTION WITH EXTENDED CORNER GUARDS)	
DH040000	1	1	MODULE BODY FENDERS: stainless steel Rear wheel housings shall have stainless steel flare skirts to protect the wheel house opening and side body finish.	
DH04RP00	1	1	POLISHED STAINLESS LOWER BODY RUB RAILS Polished stainless lower body rub rails, with #8 mirror finish, are to be along the bottom of the body on each side.	
DH100000	0	5	STAINLESS COMPARTMENT SILL PLATES: Stainless steel compartment sill plates shall be installed as noted below. (Pricing is per compartment) 5/21/2014 Locate: ALL	
DH330000	1	1	REAR DOOR HOLD OPENS, GRABBER Install chrome Cast Products "Grabber" style rear door hold opens. (NOTE: HOLD OPENS MUST BE RELOCATED IF TELESCOPIC LIGHTS ARE ORDERED)	
DL48A000	1	1	ELECTRIC DOOR LOCKS: access doors Install power activated door locks on all patient area access doors. Locks to be activated by a switch at each patient area door, and controlled with the access door locks. Locks may be overridden by a manual slide lever or by the door key. A separate lock switch will be located in the front radio console if option DL48D000 (wired to OEM locks) is not selected.	
DL48B000	0	1	ELECTRIC DOOR SWITCH: concealed Install a concealed switch on the exterior of the vehicle to operate the power door lock circuit. Doors shall be wired to unlock only on this circuit. 12/18/2015 Locate: DRIVER SIDE OF CHASSIS GRILLE	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
DL48D000	0	1	ELECTRIC DOOR LOCKS WIRED TO OEM SWITCHES The module door locks and compartment locks (if ordered) are to be wired to the chassis door lock switches. 11/29/2006	
DM100000	1	1	REFLECTORS: All patient compartment entry doors shall have red reflectors in the lower corner.	
DR220000	1	1	RUBBER MATTING IN EXTERIOR COMPARTMENTS Ribbed rubber matting will be installed on the floor and shelves of all exterior compartments.	
DR23A000	1	1	RUBBER COVERED WALLS IN BACKBOARD COMPARTMENT The interior of the backboard compartment is to be covered with rubber matting to protect equipment stored in this area. 12/30/2013 Color: BLACK	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

DSP00001 0 1 SPECIAL INSTRUCTION, MODULE BODY HARDWARE

1/5/2017 INSTALL FDNY/DC FIRE RED/WHITE "DOT" REFLECTIVE STRIPING INSIDE ALL COMPARTMENTS AND ON MODULE ENTRY DOORS. SIZE AS FOLLOWS:
SIDE ENTRY DOOR
50" VERTICALLY
12" HORIZONTALLY
- FORMS AN "L" AT THE TOP RIGHT CORNER OF DOOR
REAR ENTRY DOORS
12" STRIP MOUNTED HORIZONTALLY AT TOP OF DOOR
- PLACE RIGHT EDGE UP AGAINST EXISTING REFLECTOR
6" STRIP MOUNTED VERTICALLY ON RIGHT EDGE OF DOOR
- PLACE TOP EDGE AGAINST EXISTING REFLECTOR
12" STRIP MOUNTED HORIZONTALLY AT BOTTOM OF DOOR
- PLACE RIGHT EDGE UP AGAINST EXISTING REFLECTOR
6" STRIP MOUNTED VERTICALLY ON RIGHT EDGE OF DOOR
- PLACE BOTTOM EDGE AGAINST EXISTING REFLECTOR

COMPARTMENT DOORS TO HAVE CUSTOM STRIPS INSTALLED VERTICALLY, CENTERED TOP TO BOTTOM ON INNER PANEL OF REAR FACING DOORS, EXCEPT BATTERY. INSTALL ON LEFT EDGE OF DOORS ON STREETSIDE COMPARTMENT INNER DOOR PANELS AND RIGHT EDGE OF DOORS ON CURBSIDE COMPARTMENT INNER DOOR PANELS. SEE BELOW FOR APPROXIMATE SIZES.

O2 COMPARTMENT DOOR
50" STRIPE MOUNTED VERTICALLY, CENTERED TOP TO BOTTOM ON LEFT EDGE OF DOOR
#2 COMPARTMENT
20" STRIPE MOUNTED VERTICALLY, CENTERED TOP TO BOTTOM ON LEFT EDGE OF DOOR
STREETSIDE REAR COMPARTMENT
45" STRIP MOUNTED VERTICALLY, CENTERED TOP TO BOTTOM ON LEFT EDGE OF DOOR
BACKBOARD COMPARTMENT
50" STRIP MOUNTED VERTICALLY, CENTERED TOP TO BOTTOM ON RIGHT EDGE OF DOOR
RIGHT FRONT COMPARTMENT DOOR
50" STRIPE MOUNTED VERTICALLY, CENTERED TOP TO BOTTOM ON RIGHT EDGE OF DOOR

REAR DIAMOND PLATE RISER
50" MOUNTED HORIZONTALLY, BELOW THE LICENSE PLATE AND TOP OF REAR STEP/BUMPER

!!! DUPLICATE OF PREVIOUS VEHICLES.

DSP00002 0 1 SPECIAL INSTRUCTION, MODULE BODY HARDWARE

1/5/2017 FESCO to install a Customer supplied Life Pack Bracket.

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
DSP00003	0	1	SPECIAL INSTRUCTION, MODULE BODY HARDWARE 1/5/2017 FESCO to install two (2) Customer supplied SCBA Brackets.	
DSP00004	0	1	SPECIAL INSTRUCTION, MODULE BODY HARDWARE 1/5/2017 FESCO to supply and install four (4) heavy duty seat belt retaining straps with metal buckles.	

E PAINT AND STRIPING

ED010000	1	1	CHASSIS PAINT: standard white Chassis color to be standard white.	
ED040000	1	1	MODULE PAINT: standard white Paint module standard white Sikkens #FLNA4002.	
ED5D0000	0	1	SCOTCHLITE CHEVRONS-ENTIRE REAR Install Scotchlite chevron striping on the entire rear of the body inboard of the corner posts and below the upper driprail. 1/10/2017 Colors: Ruby Red/Lemon Yellow	
ESP00001	0	1	SPECIAL INSTRUCTION, PAINT & STRIPING 1/8/2017 There shall be a 10" Lemon Yellow Scotchlite stripe beltline stripe on the sides of the unit wrapping around the rear vertical extrusions. A Lemon Yellow Scotchlite forward sloping, upsweep stripe shall be installed on the bodysides. The main stripes shall have a .25" Blue Scotchlite outline.	

F INTERIOR CABINET DOORS, HANDLES & HARDWARE

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
FE010000	1	1	FULL HEIGHT PULL HANDLES ON SLIDING PLEXIGLAS DOORS All sliding cabinet doors to have full length pull handles.	
FE01FW00	0	1	LATCHES, NFPA STYLE, SPRING LOADED LEVER TYPE Install spring loaded lever style latches on the interior cabinets to meet NFPA 1917 standards. 5/12/2015 NOTE: DO NOT MOUNT LATCHES AT THE BOTTOM OF THE LOWER CABINET DOORS.	
FE02A000	1	1	PLEXIGLAS COLOR: light tint All Plexiglas doors to be light tint. 1/5/2007	
FE06E000	0	1	COUNTERTOP, SOLID SURFACE Install solid surface countertop in lieu of standard stainless steel. Counter is to include radiused and tapered corners. 3/9/2016 Color: MIDNIGHT PEARL !!! NOTE LENGTH OF COUNTER. COUNTER TO BE FLAT, NO LIPS FROM END OF INHALATION PANEL REARWARD TO DUPLICATE VEHICLE #16389. PHOTO IN FILE.	
FE08ST00	1	1	INHALATION PANEL (STANDARD): The inhalation panel is to be fabricated from composite material and covered with Formica to match to color selected. 7/28/2014 !!! PANEL TO BE SHORTENED 26" PER DRAWING.	

G INTERIOR COLORS, UPHOLSTERY AND SEATING

GF01R000	0	1	INTERIOR COLOR SCHEME: Custom Interior colors are as follows:	
11/29/2006	Floor:	LONCOIN LONPLATE II GUNMETAL 424		
	Risers:	WILSONART INDIGO D379		
	Walls:	WILSONART DESIGNER WHITE D354		
	Cabinets:	FASHION GRAY PAINT		
	Upholstery:	SPRADLING PRELUDE COBALT BLUE #1016		
	Accent Stripe:	WILSONART BRITTANY BLUE D321		

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
GF02M000	1	1	INSIDE CABINET FINISH: paint The interior of all aluminum cabinets shall have a durable paint finish. The painted surface shall be washable and non-absorbent. See the appropriate Interior Color Scheme option for paint color information.	
GF02P000	1	1	RISERS: The interior of this vehicle is to contain no wood or wood products. The risers are to be made of reinforced structural composite board covered with Formica per the color description. Formica will not be installed on the risers if stainless steel riser options are selected.	
GF03C000	0	1	STAINLESS STEEL LOWER DOOR PANELS Finish lower section of inside patient compartment doors with stainless steel. If an interior accent stripe is ordered the stainless is to stop at the bottom of the stripe.	
11/29/2006				
GK12A300	0	1	HIGH BACK ATTENDANT SEAT WITH CHILD SAFETY, 4PT Delete the boxed in attendant seat cushions. Install a USSC high back bucket seat with integral 4pt seatbelt and child safety seat. The seat to be adjustable front to rear.	
9/2/2015				
GK150000	5	3	SEAT BELTS: Install standard 4pt seatbelts per quantity and locations selected.	
9/2/2015 Locate:				
Head of bench				
Foot of bench				
CPR seat				
Note: Head of bench requires Option #IG070000 (Squad bench end restraint for use with HOPS)				

H

INTERIOR CABINETRY, STREET SIDE

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

HK000000 1 1 LINEN CLOSET

Install a vertical storage cabinet behind the attendant seat. The upper storage area shall house the primary electrical distribution area. The lower section shall be used for miscellaneous storage. Each area shall be accessed through hinged doors. The electrical distribution area shall include a Southco key lock/latching device. The entire cabinet shall be fabricated from aluminum and shall then be painted, unless otherwise specified.

8/12/2009

HK001000 1 1 HOPS SYSTEM:

The unit is to be equipped with the HOPS system.

Note: Deletion of the system along with the selection of option #HK01A000 requires that the credit provided under HK01B000 be deleted.

HK001B00 1 1 RADIUS STYLE CABINET TRIM

Install smooth 1.5" radiused trim on all applicable interior cabinets.

HK01B000 1 1 STREETSIDE WALL WITH CPR SEAT

Street side wall to have CPR configuration. All cabinets over 14"H will include (1) standard adjustable shelf.
SEE DRAWINGS

12/18/2015 Configure: Street side cabinets to be 18" deep.

!!! CUSTOM CABINET WALL.

!!! INHALATION CABINET TO BE 4" TALLER THAN STANDARD.

!!! CPR SEAT TO BE 32" WIDE AND LOCATED AS FAR REARWARD AS POSSIBLE. FORWARD CABINETS TO BE EXTENDED TO CPR SEAT. NOTE LENGTH OF INHALATION PANEL PER DRAWING.

HK01R000 0 3 LIFT UP CABINET FRAMES: street-side

Fasten the Plexiglas door frame extrusion to a piano hinge secured to the cabinet wall. The complete frame and doors shall hinge open upward providing total access to the cabinet behind. The frame shall be held open with gas charged cylinders and secured in the down position with a sliding dead bolt.

6/30/2014 Locate: ALL SLIDING PLEXIGLAS CABINETS

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

HK12S000 0 1 IV WARMER, SMITHWORKS

A Smithworks IV warmer will be installed in the designated area. The warmer will be wired to 12V ignition activated power, and be shoreline activated. Requires (1) 12v outlet per option PAL31C00.

1/10/2017 Location: ON THE TOP SHELF OF THE LINEN CABINET BELOW THE ELECTRONICS CABINET.

HK17G000 0 1 SHARPES/WASTE STORAGE IN A TIP OUT DOOR IN MAIN CABINET WALL

Install both sharps and waste containers on a tip-out door within the main cabinet wall. The door shall be specifically located as noted below.

5/17/2010 Location: FORWARD OF CPR SEAT PER DRAWING
!!! WASTE CONTAINER TO BE HORTON FABRICATED.

INTERIOR CABINETS AND SQUAD BENCH, CURB SIDE

IA200000 1 1 SQUAD BENCH STORAGE:

Storage shall be provided under the bench cushions. The area shall run where possible under the bench. The storage pan shall be fabricated from aluminum and shall be accessed by raising the split cushions.

1/5/2007 !!! CUSHION TO BE ONE PIECE.

IG05F000 0 1 SQUAD BENCH: DELETE CUPS AND WELLS

A 22" wide x 72" long bench cushion shall be provided on the curb side of the patient area. The cushion shall be split. No provisions for stretcher cups and wells are provided.

11/29/2006 !!! CUSHION TO INCLUDE 1" OVERHANG.

IG070110 1 1 SQUAD BENCH END RESTRAINT FOR USE WITH HOPS

Install a restraint that is 16" above the seating surface at the head end of the bench. Standard for use in conjunction with HOPPS 3-point seat belts.

DWG #105078

IG10A000 1 1 BENCH HOLD OPENS: gas

Install gas spring hold opens on squad bench lid.

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
IG10Q000	1	1	BENCH HOLD-DOWN: paddle latches (Pair) Install recessed paddle latches into the squad bench riser to retain the squad bench lids in the closed position. The latches shall be both passive and positive. 2/16/2016 !!! INSTALL ONLY (1). CUSHION IS ONE PIECE.	
IG15A000	1	1	BENCH CUSHION EDGE TRIM: Trim bench cushion edge with protective aluminum trim, to protect horizontal edge of squad bench cushion from tears..	
IG15B000	1	1	BENCH BACK CUSHION: full size Delete individual squad bench back cushions. Install full size cushion. 6/30/2014	
IK18AA00	1	1	CURBSIDE OVERHEAD CABINET: hinged doors Storage shall be provided above the squad bench. The storage shall run the full length of the squad bench and shall be accessed through hinged Plexiglas doors that are held in the open position with gas activated rods. The entire cabinet shall be fabricated from aluminum. The cabinet is to be 9" H to meet current K requirements. 2/16/2016 NOTE: INCREASE THE DEPTH OF THE CABINET 2" FROM STANDARD. !!! NOTE LOCATION OF 02 OUTLET AT FORWARD END.	
IK29A000	0	1	GLOVE STORAGE ABOVE SIDE ENTRY DOOR Install recessed storage above the side access door for two (2) boxes of gloves. Provide oval openings in a hinged padded and upholstered door for glove access. Note: Reduce the height of the front wall cabinet 1.00" to accommodate this option. 2/16/2016 Storage shall be for three (3) boxes of gloves. Glove box size: 10.5" X 5.5" X 4.0"	
ISP00001	0	1	SPECIAL INSTRUCTION, CURBSIDE CABINETRY 1/10/2017 !!! INSTALL A SHARPS WASTE CABINET AT THE HEAD OF BENCH PER DRAWING. TOP OF THE CABINET TO HAVE RED SLIDING FORMICA COVERED ALUMINUM DOORS FOR ACCESS TO THE CONTAINERS. INCLUDE A LIFT-UP FRAME. TOP OF THE CABINET TO BE FLUSH WITH THE BENCH CUSHIONS. COVER DOORS WITH RED FORMICA. SUPPLY AND INSTALL A SAGE #8970 SHARPS CONTAINER LONG WAYS FROM THE FRONT TO THE REAR AS CLOSE TO THE AISLE EDGE OF THE BENCH AS POSSIBLE. WASTE CONTAINER TO BE SAME MINUS LID.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

J	INTERIOR CABINETS, FRONT			
---	--------------------------	--	--	--

JAK03DP0 0 1 FRONT WALL CABINET, DIAMOND PLATE INTERIOR:

The front wall cabinet shall be constructed of aluminum diamond plate instead of flat painted aluminum. All shelves in the cabinet shall also be made of diamond plate.

2/16/2016 !!! INSTALL A SLOTTED VENTILLATION GRILLE ON THE LEFT (INBOARD) SIDE OF CABINET. TO BE INSTALLED THROUGH-BOLTED WITH CHROME ACORN NUTS ON INSIDE OF CABINET.

!!! SHELF ABOVE THE DRAWER TO BE WELDED IN ILOS.

!!! INVERT BOTTOM SHELF.

JE040000 4 2 FRONT WALL DOORS: Plexiglas

Front cabinet wall to have hinged Plexiglas doors, and latch type as designated.

5/21/2014 !!! LOWER PORTION

JE05R210 0 1 ROBINSON ROLL UP DOOR, HALF HEIGHT

A half height Robinson roll up door shall be provided. The door is to include a lift bar latch with key lock.

1/19/2017 Size: Upper half of the front wall cabinet above the drawer.

!!! A CUSTOMER SUPPLIED MEDECO Classic CLIQ Cam Lock shall be sent to rom for installation in the roll-up rom door.

JK040000 0 1 PULL OUT DRAWER IN FRONT WALL CABINET

A pull out drawer will be installed in the front wall cabinet.

1/19/2017 SIZE: 6" ID

!!! THE DRAWER SHALL BE CENTERED IN THE FRONT WALL CABINET BELOW THE ROM ROLL-UP DOOR.

A SIMPLEX #900 SERIES COMBINATION LOCK SHALL BE MOUNTED ON THE DRAWER OF THE FRONT WALL CABINET.

K	MODULE INTERIOR ACCESSORIES AND TRIM			
---	--------------------------------------	--	--	--

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
KG02B000	2	3	IV HANGER, CAST PRODUCTS WITH RUBBER ARM Cast products recessed IV hangers with rubber arms for attaching solution bags shall be installed in the designated locations. 9/26/2012 Locate: HEAD AND FOOT OF COT MIDSECTION OF BENCH, AISLE EDGE	
KG09F000	0	1	GRAB RAIL: 8ft with anti-microbial coating Install 8 foot main grab rail with anti-microbial coating. 7/21/2014 Locate: OVER COT	
KG09I000	0	1	VERTICAL GRAB RAIL INSTALLATION, 2 FT. ANTI-MICROBIAL Install 2' stainless steel grab rail with anti-microbial coating. 7/21/2014 Locate: STEPWELL SIDE OF HOPS BOLSTER PER DRAWING	
KG09K000	1	1	PATIENT DOOR GRAB RAILS: angled with anti-microbial coating All patient access doors to have heavy duty angled stainless steel grab rails with smooth radius corners and flange mounting and anti-microbial coating.	
KG110000	1	1	FLOOR TRIM Trim floor with cove molding at non rolled areas of floor.	
KG120000	1	1	CABINET TRIM Trim all vertical and horizontal edges.	
KG16B000	1	1	CEILING MATERIAL, PLATINUM WHITE ALUMINUM COMPOSITE The standard module ceiling material shall be platinum white aluminum composite.	
KG17A000	2	2	FIRE EXTINGUISHERS: 5lb ABC Supply five pound fire ABC extinguisher(s). Ship loose, or identify mounting location(s). 11/2/2012 !!! INSTALL AT FINAL INSPECTION.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

L	COT MOUNTS AND ACCESSORIES			
----------	-----------------------------------	--	--	--

LG03F300 0 1 COT MOUNT, INSTALL Power Load
Supply and install a Stryker Power load system.
Note: This option complies with GSA change notice 8.
6/13/2015 !!! Requires selection of option #CB07E000

LG040000 0 1 SUPPLY COT:
Supply and install new cot.

**CUSTOMER
SUPPLIED**

1/10/2017 Cot Model: Stryker PowerPro Cot with PowerLoad compatibility upgrade.

M	LIGHTBARS FRONT AND REAR			
----------	---------------------------------	--	--	--

12/18/2015

MAM60000 0 1 INSTALL CUSTOMER SUPPLIED TRAFFIC EMITTER
A customer-supplied traffic emitter shall be installed as noted below:
2/23/2016 LOCATION: CONSOLE
!!! ILOS, INSTALL PREWIRE ONLY AND LEAVE IN CONSOLE. WIRING TO BE COILED AND LEFT IN CONSOLE ILO FRONT FACE OF VEHICLE. LABEL "OPTICOM PRE-WIRE". TO BE WIRED THROUGH NEUTRAL SAFETY AND PROGRAMMED AS STANDARD OPTICOM PREWIRE.

MM	ELECTRICAL EMERGENCY VISUAL WARNING SYSTEMS			
-----------	--	--	--	--

MM030000 1 1 WHELEN M SERIES LIGHTING OPTIONS:
5/21/2014

0 1 M7 SERIES LED, AMBER
mm07a000 Whelen M7 series L.E.D. lights shall be installed in the designated locations.
1/3/2017 LOCATION: CENTERED OVER THE REAR ENTRY DOORS
LENS COLOR: CLEAR

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
0	8		M7 SERIES LED, RED	
mm07r000			Whelen M7 series L.E.D. lights shall be installed in the designated locations.	
1/3/2017			LOCATION: GRILLE LIGHTS, TWO OVER TWO. FLASH IN AN 'X' PATTERN. INTERSECTION LIGHTS (INCLUDE HOUSINGS AND ADAPTER PLATES) WHEEL WELL LIGHTS LENS COLOR: CLEAR	
0	14		M9 SERIES LED, RED	
mm09r000			Whelen M9 series L.E.D. lights shall be installed in the designated locations.	
1/3/2017			LOCATION: (6) FRONT FACE OF THE MODULE, THREE EACH SIDE OF THE CENTER CLEAR (2) EACH UPPER BODY SIDE (2) REAR WINDOW LEVEL (2) UPPER REAR CORNERS, ONE EACH SIDE LENS COLOR: CLEAR	
0	1		M9 SERIES LED, WHITE WITH CLEAR LENS	
mm09w000			Whelen M9 series L.E.D. lights shall be installed in the designated locations.	
2/16/2016			LOCATION: CENTERED ON THE FRONT FACE OF THE MODULE. !!! INCLUDE A SWITCH FOR LIGHT TO STEADY BURN AND LABEL 'TAKE-DOWN'.	
MM10M000	0	3	L.E.D. WARNING: patient entry door, DUAL color (EACH) Install custom made L.E.D. light strips on the interior patient entry door panels. The lights are to have 3" sections of alternating light colors as noted below. The light strips shall have a integral lens strip for maximum light disbursement. Installation will be flush with the inner door panel. The light strip shall flash when the door is open, and the red flashing light circuit is activated.	
3/9/2016			RED/WHITE: <u>XXX</u> Color: RED Location: UPPER PORTION OF PATIENT ENTRY DOORS !!! LIGHTS TO FUNCTION REGARDLESS OF MODULE DISCONNECT SWITCH POSITION AND ALTERNATE FLASH.	
MM7A0000	0	1	M Series control wire The selected M Series lighting is to feature pattern programmability from the control panel. Include pattern and sync wires in the harness.	
1/13/2017			Lights: All	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
MM800000	0	1	WHITE LIGHT CUTOFF SWITCH A switch shall be installed in the front control panel that will deactivate all forward facing white flashing lights. This include wig-wag flashers if ordered. 1/13/2017	
MMSP0010	0	1	SPECIAL INSTRUCTION, VISUAL EMERGENCY WARNING SYSTEMS 1/13/2017 !!! PROGRAM ALL UPPER WARNING LIGHTS FOR WHELEN "ACTION FLASH #150". SET THE LOWER WARNING LIGHTS TO WHELEN "TRIPLE FLASH 120".	
MN AUDIBLE EMERGENCY WARNING SYSTEMS				
MN35CA00	0	1	SIREN, WHELEN #295SLSA1 A Whelen #295SLSA1 siren shall be installed. 12/23/2013	
MN40A000	1	1	SIREN INSTALL: The siren listed above shall be supplied and mounted as defined. 11/29/2006	
MN45DH00	1	1	SIREN SPEAKERS: C.P. SAD3806 & SAP3806 RECESSED IN BUMPER Cast Products #SAD3806 & SAP3806 siren speakers shall be recess mounted into the ends of the chassis bumper. For use with current model F-Series chassis.	
MN50A000	1	1	SPEAKER INSTALL: bumper Speaker Selections (Bumper Installed)	
O LIGHTS				

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
OL09M000	0	1	KKK SIDE BODY MARKER LIGHTS, M6 SERIES L.E.D. (PAIR) Install red Whelen L.E.D. M6 series turn/marker lights on each rear side of the module body. Lights provide module body night time side lighting visibility and turning signal indication. 12/23/2013	
OL34L000	1	1	LED EXTERIOR COMPARTMENT LIGHTING All exterior compartments will be lighted with LED strip lighting. A vertical strip will be installed inside both sides of each compartment. The lights shall be directed toward the back of the compartment.	
OM25CW0	0	6	M9 SERIES LED SCENE LIGHT Install Whelen M9 series LED side scene lights. 5/21/2014 LOCATE: (2) PER BODY SIDE AS SCENE LIGHTS (2) OVER REAR DOORS AS LOADING LIGHTS	
OM30D000	0	1	TAIL LIGHTS, M6 SERIES Whelen M6 series brake/tail, amber arrow turn and backup lights to be installed in the selected location. 5/21/2014 Locate: STACKED ON REAR ABOVE RISER	
OM30FB00	0	1	AMBER ARROW LIGHTS, M6 SERIES LED's Whelen amber arrow M6 series led lights shall be installed in the designated location. 12/18/2015 LOCATE: FRONT FACE BELOW THE OUTBOARD RED WARNING LIGHTS	
OSP00001	0	1	SPECIAL INSTRUCTION, ELECTRICAL 5/21/2014 !!! ILOS ALL ICC MARKER LIGHTS TO BE TRUCK-LITE #35375R OR Y AS REQUIRED BY LAW.	
OSP00002	0	1	SPECIAL INSTRUCTION, ELECTRICAL 5/21/2014 !!! THE LICENSE PLATE LIGHT TO BE A TECNIQ #L11-WC00-1.	

P	ELECTRICAL POWER GROUP
----------	-------------------------------

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
PAL00006	1	1	INTELLIplex i4G: Install the Intelliplex i4G electrical system. System is to include a USB port installed under the dash for ease of programming. 10/13/2015	
PAL00010	0	1	COOL TECH II Install wiring and Eco Smart fan control module for use with Cool Tech II unit. Solar panel wiring is to be included. 2/16/2016 !!! COOL TECH III !!!	
PAL00A00	0	1	MODULE DISCONNECT DEFAULT The module disconnect circuit shall default to the "on" position when the battery switch is activated. 10/13/2015	
PAL01C00	0	1	INPOWER ELECTRONIC BATTERY SWITCH Install an Inpower electronic battery switch. Switch is to activate battery power through the vehicle ignition and is to include an automatic shutdown timer to deactivate battery power after the ignition is turned off. 1/5/2017 Shut down timer interval: 5 minutes !!! OPTION PL11E000 IS NOT APPLICABLE IN CONJUNCTION WITH THIS OPTION.	
PAL02200	1	1	INVERTER INSTALL OPTIONS: 7/23/2010	
pal02k00	0	1	INVERTER:20-1050CUL w/charger, interface A Vanner #20-1050CUL combination inverter /charger shall be installed in the vehicle's designated electrical equipment location. Included will be a Vanner Interface Module, Inverter Status Panel, and Charger Status Panel. A switch will be installed in the inhalation panel for inverter activation. The charger will be wired to the shoreline circuit. 5/21/2014 !!! INSTALL INVERTER STATUS PANEL ON INHALATION WALL AND CHARGER STATUS PANEL ON STREETSIDE OF BODY PER DRAWINGS.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
PAL30A00	2	3	110V INTERIOR OUTLET Two 110V interior outlets are provided as standard on all models. The standard locations are in the inhalation area and the wall over the squad bench. List the standard outlet locations and any deviation from the standard, plus any additional outlet locations below: 7/21/2014 LOCATE: INHALATION WALL PER DRAWING LOCATE: DOUBLE DUPLEX, FRONT WALL CABINET PER DRAWING	
PAL31C00	3	5	INTERIOR 12VDC OUTLETS: cigarette lighter type 12 volt outlets to use cigarette lighter style connectors. 1/10/2017 LOCATE: INHALATION PANEL Locate: INHALATION PANEL (KUSSMAUL USB Dual Port, Model #: 091-219) LOCATE: FRONT WALL CABINET, LOWER PORTION LOCATE: CONSOLE EXTENSION, FORWARD END TOWARDS PASSENGER LOCATE: LINEN CABINET BEHIND THE ATTENDANT'S SEAT (LOCATE ABOVE THE TOP SHELF IN THE LOWER SECTION) Configure: BATTERY HOT	
PAL38C00	0	2	SHORELINE: 20 amp eject Install a 20 amp Kussmaul auto ejection shoreline receptacle. Include a dynamic disconnect. 6/30/2014 Locate: street side module body !!! DEDICATE ONE FOR 110V HEAT/AC, HORTON RECOMMENDS A 30 AMP SHORELINE)	
PAL38IL0	0	1	SHORELINE INDICATOR: Install an indicator pilot light to show power to A.C. circuits and presence of activated shoreline. 10/13/2015 Locate: ABOVE THE SHORELINE INLET FOR THE 110 VOLT A/C SYSTEM Configure: LED	
PAL40000	1	1	EXTRA 12VDC CIRCUIT BREAKER: An extra circuit breaker shall be installed.	
PL10A000	1	1	SWITCH PANEL MOUNT: Switch panel to be flush mounted in upper face of console.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
PL11A000	0	1	LIGHT PROGRAMMING: side rear scene The side rear scene lights shall be wired to transmission reverse, plus standard mode of operation. 11/29/2006	
PL11B000	0	1	LIGHT PROGRAMMING: right side scene The right side scene lights shall come "on" when the side patient door is opened. 11/29/2006	
PL11C000	0	1	LIGHT PROGRAMMING: load light The rear load lights shall be wired to transmission reverse, plus the standard mode of operation. 11/29/2006	
PL11F000	1	1	PROGRAMMING: AUDIBLE LOW VOLTAGE ALARM Program an audible alarm to activate if the voltage drops below 11.8 volts for 120 seconds.	
PL11G000	1	1	LIGHT PROGRAMMING: park brake A warning shall display on the front console readout, advising to set the Parking Brake, should the modular disconnect switch be "ON" and the transmission placed in "PARK" or "NEUTRAL". It will also advise to Disengage the Parking Brake should the vehicle be placed into gear. Configure: wire alarm to activate with red flasher circuit	
PL19A000	1	1	REPORT LIGHT Install a 12" Tecnique LED bar style report light. 5/21/2014 !!! INSTALL A TECNIO #E35-WB00-1, 12.6" LED LIGHT.	
PL20E000	0	1	CLOCK, INTELLITEC LED Install an Intellitec Time Manager clock. 5/21/2014 LOCATE: INHALATION PANEL	
PL22C000	1	1	STEP WELL LIGHT: Install a 10.5" LED Vista light strip in the standard location on the bench side of the step well. Light to activate with door open.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
PL23A000	0	1	2.5" CAB CEILING LIGHTS, COMBINATION WHITE/RED LED LED lights shall be installed in the cab headliner above the driver and passenger seats. Each light contains a combination of white and red LED's which will be switched separately in the front control panel. 2/16/2016 MANUFACTURER #E13-WSOR-1 LIGHTS WITH CHROME TRIM RING #E13-WS001 !!! PROVIDE SEPARATE SWITCHES FOR THE RED AND CLEAR LIGHTING ON THE SWITCH CONTROL PANEL.	
PL23AB00	0	1	NFPA CAB WARNING LIGHT Install a red LED warning light within sight of the driver. Wire to flash when the ignition is 'on' with the emergency brake disengaged and a door is open. This is in addition to the standard operation. 2/16/2016 LOCATE: CONSOLE LEFT OF SIREN TO DUPLICATE PREVIOUS VEHICLES	
PL24T000	0	1	LAMP TIMER: programmable Install an electronic momentary touch timer switch where specified. The switch will enable time limited operation of the below listed lights, with the battery switch in the off position. 7/21/2014 Locate: STEPWELL SIDE OF HOPS BOLSTER Light(s) Controlled: DOMES SET ELAPSED TIME FOR 15 MINUTES	
PL27CA00	0	9	PATIENT CEILING DOME LIGHTS: WHELEN LED Install Whelen 80C0EHCR LED dome lights in the patient area ceiling per the locations listed below. The lights will have a high/low feature with the switch in the rear control panel. 5/21/2014	
PL27FS00	0	1	LIGHT PROGRAMMING: cab light control The following lights shall be controlled as follows in addition to the standard modes of operation; A switch on the front control panel can be toggled to turn off the defined lights, should they be on. The switch can also be toggled to turn on the defined lights, should they be off. 5/9/2014 Lights: patient dome lights	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
PL29C000	0	4	HAND LIGHTS: SL-45 Horton install HORTON to supply and install SL-45 box light(s). 1/19/2017 Quantity: Two (2) Locate: WALKTHROUGH, CLOSEOUT ON PATIENT SIDE UPPER LEFT PORTION OF STREETSIDE INTERMEDIATE COMPARTMENT LIGHTS TO BE FIRE VULCAN LED STYLE. MOUNT ON THE FINAL INSPECTION. Quantity: Two (2) Locate: UPPER RIGHT PORTION OF STREETSIDE INTERMEDIATE COMPARTMENT LIGHTS TO BE STREAMLIGHT SURVIVOR #90509 LED TYPE. MOUNT ON THE FINAL INSPECTION.	
PM110000	0	1	LIGHT PROGRAMMING: brake light Lower red flashing lights to operate as brake lights when not in the warning mode. 11/29/2006 Configure: BRAKE LIGHTS TO OVERRIDE FLASHERS Note: feature to activate regardless of module disconnect status	
PM490000	0	1	SECURITY IDLE SYSTEM: Install a secure idle system to allow engine operation with transmission in park and ignition key removed. If the brake is depressed or transmission attempted to be shifted into gear, the engine will shut off, the marker lights will flash and the horn will sound. The system will be integrated into the HORTON system 2000 and Intelliplex electronic systems, be activated by a switch on the control panel and provide a digital display to warn of the activated security mode. 7/21/2014	
PSP00001	0	1	SPECIAL INSTRUCTION, ELECTRICAL POWER, PROGRAMMING 1/5/2017 !!! INCLUDE A SWITCH IN FRONT CONTROL PANEL TO OVERRIDE SIDE SCENE LIGHTS WHEN PATIENT ENTRY DOORS ARE OPENED.	
PSP00002	0	1	SPECIAL INSTRUCTION, ELECTRICAL POWER, PROGRAMMING 1/5/2017 !!! SUPPLY AND INSTALL A KUSSMAUL DUAL USB PORT ON CONSOLE PER DRAWING.	
Q HEATING, AIR CONDITIONING AND INTERIOR ENVIRONMENT				

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

QH29F100 1 1 HEAT/AC SYSTEM FORD F SERIES CHASSIS

Install a ProAir 12V heat/AC system below the attendant seat. Unit is to include a replaceable filter at the air intake point.

3/9/2016

QH29F480 0 1 COOL TECH III CONDENSER

Install a ProAir Pre-charged 12V heat/AC system below the attendant seat. Unit is to include a replaceable filter at the air intake point.

Install a Cool Tech III 4-fan 100,000 BTU condenser in the recessed pocket on the roof of the body. Unit to include a single fan 40,000 BTU condenser for the 110V AC ordered separately.

10/13/2015 Note: Requires option # CB120000 & PAL00010 and selection of a 110V option.

QH29F500 1 1 RECEIVER/DRYER KIT, ALL FORD F-SERIES CHASSIS

Receiver/dryer kit #80-001-949 w/pressure switch shall be installed in the air conditioning system.

QL43N000 1 1 NFPA COMPLIANT VENTING-CAST VENTS

Install an NFPA style venting system to include a 400cfm exhaust vent along with a static vent. Install 9.5" square polished covers on both vents per drawings.

2/16/2016 !!! INCLUDE SWITCH ON STEPWELL SIDE OF BOLSTER TO DUPLICATE PREVIOUS VEHICLES.

QL455000 0 1 DANHARD 110V A/C SYSTEM

Install a Danhard 50-2000 110V heat/AC unit as noted below.

12/18/2015 NOTE: MAY REQUIRE ADDITIONAL CABINET MODIFICATION FOR CHANGEOVERS.
THERMOSTAT LOCATION: INHALATION WALL

!!! LOCATE THE UNIT UNDER THE CPR SEAT.

R CAB CONSOLE AND COMMUNICATIONS

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
RJ030000	0	2	ANTENNA 1: Supply and install a K-94 mount and coax. 1/3/2017 ANTENNA #1: EXTERIOR TERMINATION: STREETSIDE FRONT OF MOD ROOF PER DRAWING INTERIOR TERMINATION: BEHIND PASSENGER SEAT ANTENNA #2: EXTERIOR TERMINATION: CURBSIDE FRONT OF MOD ROOF PER DRAWING INTERIOR TERMINATION: BEHIND PASSENGER SEAT	
RJ040000	1	1	RADIO CABLE PULL WIRE A standard pull wire for radio installation shall be installed from behind the driver's seat to behind the inhalation panel. 9/14/2009 Location: Behind the driver's seat Terminate: Behind the inhalation panel	
RJ05B000	1	1	FRONT CONSOLE: A console shall be fabricated to coordinate with the interior cab color. Room shall be provided on the face of the console for installation of radio and siren controls. 2/16/2016	
RJ05C000	0	1	CONSOLE EXTENSION: A box for mounting radio heads and storage maps, books, or binders will be attached to the standard engine cover console. Standard box includes (3) 2.5 storage sections, and 8.5 faceplate for radio mounting. 1/8/2017	
RJ05CP00	0	1	CUP HOLDERS Install two (2) cup holders recessed into the console per drawing. 5/11/2015	
RJ06A000	0	1	RADIO HEAD PRE-CUT: front Cut out control console for radio head(s). 1/13/2017 Install Customer supplied radio faceplate on the cab console.	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
RJ06B000	0	1	RADIO HEAD PRE-CUT: rear Cut out rear action panel for radio head(s). 1/13/2017 Install Customer supplied radio faceplate on the inhalation panel radio plate.	
RJ070000	0	1	RADIO CABLE INSTALL: customer supplied Customer supplied radio cables will be installed during the vehicle construction. Cables to be tagged and marked at each end to identify their installed location. All cables shipped to Horton must have the vehicle production number clearly marked on the shipping package, and delivered prior to or at time of modular pre-wire. 5/11/2015 Locate: INHALATION Termination: BEHIND PASSENGER SEAT	
RJ08A000	0	2	RADIO POWER/GROUND: Install three 6 gauge cables to positive and ground studs for radio power. Wire one constant hot, one ignition hot and one ground. 1/2/2014 LOCATE: CAB CONSOLE AND BEHIND THE INHALATION PANEL	
RSP00001	0	1	SPECIAL INSTRUCTION, CAB CONSOLE & COMMUNICATIONS 1/8/2017 !!! SUPPLY AND INSTALL A BLANK RADIO PANEL IN THE INHALATION PANEL PER DRAWING.	
RSP00002	0	1	SPECIAL INSTRUCTION, CAB CONSOLE & COMMUNICATIONS 1/8/2017 !!! FABRICATE AND INSTALL PADDED ARM RESTS MOUNTED ON THE RIGHT AND LEFT SIDES OF THE CAB CONSOLE EXTENSION.	
T OXYGEN AND SUCTION				

TN002000	1	1	OXYGEN BOTTLE MOUNT, VERTICAL TRACK FOR QRM-V Vertical track for mounting of a QRM-V O2 bottle mount shall be welded on the back wall of the compartment in the right hand corner. The O2 bottle mount is adjustable for "M" or "H" size tanks. 1/9/2014	
----------	---	---	---	--

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
TN01MW00	1	1	OXYGEN BOTTLE, CYLINDER BRACKET: Zico Zico QRM-V oxygen bracket shall be installed. 6/30/2014 Locate: STREETSIDE FRONT COMPARTMENT Tank Size: "M"	
TN030000	2	2	OXYGEN OUTLETS, STANDARD Two oxygen outlets to be provided as standard and located in the inhalation panel unless relocated per option TN03RL00. 1/10/2017 ONE OF THE MAIN WALL O2 OUTLETS SHALL BE A DISS CONNECTION. SET FOR 55 PSI.	
TN03A000	0	2	OXYGEN OUTLET: additional Install additional oxygen outlet(s). 1/3/2017 Locate: FORWARD END OF BENCH CABINET AND CEILING OVER THE COT.	
TN04A000	1	1	ADAPTER TYPE: Ohio Diamond II Oxygen outlets to be Ohio Diamond II. 11/29/2006	
TN060000	1	1	OXYGEN WRENCH: Install oxygen wrench in oxygen compartment. Mount secure so not left hanging. Mount with length of chain or cable so not removable.	
TN08B000	0	2	D BOTTLE MOUNT: single, 521 model Install a F.W. #521 oxygen bracket. 1/13/2017 LOCATE: MOUNT ACROSS FROM THE LINEN CABINET.	
TN11B000	1	1	ASPIRATOR: SSCOR Install an SSCOR aspirator. The system shall include a #22000 wall mounted regulator, and a #23002 canister holder. Plumb to the pump selected. 11/29/2006	
TN12C000	0	1	VACUUM PUMP: Install a CFP #107CDC20 12vdc electric suction pump. 6/13/2015	

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017
Chassis: Ford Type I, 189" WB, 108"
Model: 603F

Option	Std	Qty	Header/Description/Data	Proposal Total
--------	-----	-----	-------------------------	----------------

TSP00001	0	1	SPECIAL INSTRUCTION, OXYGEN & SUCTION	
----------	---	---	---------------------------------------	--

5/5/2010 !!! SET THE OXYGEN LOW PRESSURE ALARM TO 300 PSI.

U LETTERING

4/20/2011

UP010000	0	1	LETTERING:	
----------	---	---	------------	--

Lettering to be included.

1/10/2017 A Graphic element shall be provided per the attached itemized sheet.

Z MISCELLANEOUS

9/12/2012

Z02	0	1	Factory Pickup and Transportation	
-----	---	---	-----------------------------------	--

Allowance for vehicle pickup, transportation and drivers fee.

1/3/2017

Z03	0	1	Dealer Prep. and Dealer Delivery	
-----	---	---	----------------------------------	--

Allowance for vehicle preparation and delivery.

1/3/2017

Virginia State Inspection

Z04	0	1	Fuel, Tags, Etc.	
-----	---	---	------------------	--

Allowance for fuel, tags and administrative.

Z05	0	1	NOTES:	
-----	---	---	--------	--

Note.

1/3/2017 !!! Concession from Dave marshall to secure order.

COUNTY OF SPOTSYLVANIA
PO BOX 215
SPOTSYLVANIA, VIRGINIA 22553
DONNA BEASLEY



Selected Feature List 15147

Year: 2017

Chassis: Ford Type I, 189" WB, 108"

Model: 603F

<u>Option</u>	<u>Std</u>	<u>Qty</u>	<u>Header/Description/Data</u>	<u>Proposal Total</u>
---------------	------------	------------	--------------------------------	-----------------------

Total Configured Cost \$250,857.00

Authorized Department Signature(s): _____

